







Power **LIGHT** System




*The multi-functional system with
perfectly coordinated modules for curing
UV-light-reactive liners*

I.S.T.
creating.value

The UV building-block system

Controllers	Drums	Booster	Light chains	Curing cameras	Wheelsets	Deflections	End caps
 <p>Compact UV system for pipes from 6" to 63" incl. controller and cable drum with up to 650' capacity</p>		 <p>Booster Mini (9 x 650 watts) for boosting the controller output</p>	 <p>Standard light chain 3600 watts (9 x 400 watt lamps) for pipes from 6" to 20" incl. oval profiles</p>	 <p>HORIZONTAL SELF-LEVELING Front camera</p>		 <p>DEFLECTION RODS – spindle spinner with outer pipe deflection rod » length 20" - 32" » length 24" - 36" » length 32" - 43"</p>	 <p>PACKERS FOR CIRCULAR PROFILES » Ø 6" » Ø 8" - 10" » Ø 12" - 15" » Ø 16" - 20" » Ø 24" » Ø 28" » Ø 32" - 36" » Ø 40" - 48" » Ø 48" - 56" » Ø 56" - 64" » plus special profiles</p>
 <p>Professional Control Cabinet for controlling light chains with various configurations and outputs up to 9 x 650 watts</p>	 <p>UV drum 1000 with cable lengths up to 1000'</p>	 <p>Booster Medium (9 x 1000 watts) for boosting the controller output</p>	 <p>Standard Plus light chain 5850 watts (9 x 650 watt lamps) for pipes from 6" to 24" incl. oval profiles</p>	 <p>WITH LIGHTING Back-eye camera</p>		 <p>DEFLECTION PULLEY for shaft opening</p>	 <p>PACKERS FOR OVAL PROFILES » Ø 16" - 24" » Ø 20" - 30" » Ø 24" - 36" » Ø 28" - 42" » Ø 32" - 48" » plus special profiles</p>
	 <p>UV drum Portable with cable lengths up to 650'</p>	 <p>Booster Maxi (9 x 2000 watts) for boosting the controller output with Maxi system configurations</p>	 <p>Medium light chain 9000 watts (3 x 3 of 1000 watt lamps) for pipes from 26" to 63" incl. oval profiles</p>	 <p>Triple Core light chain 18000 watts (3 x 3 of 2000 watt lamps) from 48" to 80" incl. oval profiles</p>		 <p>Oval profile » wheelset ø 20" - 30" » wheelset ø 24" - 36" » wheelset ø 28" - 42" » wheelset ø 32" - 48"</p>	 <p>DEFLECTION PULLEYS for retracting film and liners » Deflection pulley, width of 12" » Deflection pulley, width of 20"</p>

Protocols



Possible configurations

XS



- » Compact UV system
- » Standard light chain (3600 watts)
- 9 x 400 watt lamps for pipes from 6" to 20" incl. oval profiles



S



- » Compact UV system
- » Booster Mini (9 x 650 watts)
- » Standard Plus light chain, 5850 watts
- 9 x 650 watt lamps for pipes from 6" to 24" incl. oval profiles



M



- » Compact UV system
- » Booster Medium (9 x 1000 watts)
- » Medium light chain (9000 watts)
- 3 x 3 of 1000 watt lamps for pipes from 26" to 60" incl. oval profiles



L



- » Professional Control Cabinet
- » UV portable drum with cable lengths up to 650'
- » Booster Medium (9 x 1000 watts)
- » Dual-core light chain (8000 watts)
- 2 x 4 of 1000 watt lamps for pipes from 26" to 60" incl. oval profiles




XL



- » Professional Control Cabinet
- » UV drum 1000 with cable lengths up to 1000'
- » Booster Maxi (9 x 2000 watts)
- » Light chain Maxi (18000 watts)
- 3 x 3 of 2000 watt lamps for pipes from 48" to 80" incl. oval profiles



<i>Power LIGHT UV-Curing Control Professional</i>	
UV light output:	9 x 400/650/1000 watts — optional 9 x 2000 watts totaling 18,000 Watts
Cable length:	Up to 1020'
Protocol:	I.S.T. UV documenting system, I.S.T. UV doc recorder/player
Controls:	Siemens SPS KTP 1200 S7
Light source:	9 x 400/650 watts, 6" - 24"
	9 x 1000 W chain / 8 x 1000 W dual-core (optional), 26" - 60"
	9 x 2000 W chain, 48" - 80"
Camera system:	Self-leveling horizontal Front camera & Back-eye camera (incl. Back-eye lighting)



More information available at
www.ist-na.com

